Renolack
Exotic

PRIMING LACQUER FOR WOOD



PRODUCT INFORMATION PAGE

TECHNICAL DATA:

Nr. art. 0956

FORM:	liquid
COLOUR:	colourless
ODOUR:	specific
BOILING POINT RANGE:	82 - 122°C
IGNITION POINT:	320°C
OXIDIZING PROPERTIES:	none
DENSITY:	0,81 g/cm^3
SUITABLE FOR USE:	12 months from production date
PACKAGING SIZE:	1L, 5L

PROPERTIES:
RENOLACK EXOTIC is a universal single-component priming lacquer based on alcohol intended for priming of all wood grades, including exotic wood. It prevents wood darkening caused by surface lacquers. It insulates the surface lacquer effectively from the wood substances. It is characterised with very good wood adherence. It decreases use of floor lacquers.

APPLICATION:
For all surfaces made of soft and hard wood, parquets, mosaics, wainscots.

METHOD OF USE:
Mix the priming lacquer carefully before application. Apply with a roller or brush. The wooden surfaces must be dry, clean, free from oil, wax, dust and other contamination. Before priming the wood must be ground with sandpaper, grain 100-120. It is recommended to make a trial in a concealed spot. The surface lacquer must be applied when the primer is completely dry. Perform the work in temperate from 15°C to 25°C, relative humidity ca. 50%. Ensure proper ventilation in the room.

DRYING TIME:
30 - 60 minutes, depending on temperature and relative air humidity as well as wood grades.

STORAGE:
Store in the originally sealed packaging, in a dry place, in temperature at 5°C to 25°C.

CONSUMPTION:
100 – 120 ml/m^2

1 LITRE EFFICIENCY:
8 – 10 m^2

For difficult problem-solving questions, or products with special requirements, which are not covered by this technical card, we assure all our clients of our professional consulting services. Upon issue of a new technical card, the present one will no longer be valid.