Renoplast

D 2000

STICK ON ADHESIVE FOR FLOOR COVERING AND VINYM TILES



PRODUCT INFORMATION PAGE

TECHNICAL DATA:

Nr. art. 0996

BASE:	synthetic dispersion
COLOUR:	white
DENSITY:	1,0 g/cm^3
WORKABILITY TEMPERATURE:	at 15°C to 25°C
SUBFLOOR TEMPERATURE:	≥10°C
COVERAGE:	70 - 100 g/m^2 (concentrate)
DRYING TIME:	15 - 30 min. at the 20°C
PACKAGING:	10 kg can

PROPERTIES:
Quick drying, solvent free, sticky adhesive, (never curing) for installing vinyl tiles on porous and non-porous subfloors. Easy in application prevents creating blanc spaces - voids.

APPLICATIONS:
Thanks to its properties and structure the Renoplast D 2000 is ideal for the vinyl tiles on almost all kinds of subfloor. Replacing/moving once installed tile is possible at any time.

SUBFLOOR PREPARATION:
The subfloor should be even, dry, flat, free of dust, stabile, free of cracks and contaminations by oils, paints, gypsum and other reducing adhesion.

HOW TO USE:
The adhesive should be evenly applied by the roller. In 15 min – 30 min when the adhesive turns into translucent coat, the floor covering can be installed. Press down evenly. This adhesive can be also use for installation of antistatic floor coverings once mixed with conductive agent R 2000. Recommended ratio: 3 kg of R 2000 on 20 kg of adhesive RENOPLAST 2000. The mixed formula should be used after mixing.

STORAGE:
Keep closed in original packaging in dry conditions above 5°C to 25°C.

SHELVE LIFE:
12 months after the date on the packaging.

Accordingly to the current regulations, this product does not contain ingredients/components classified as harmful.

For difficult problem-solving questions, or products with special requirements, which are not covered by this technical card, we assure all our clients of our professional consulting services. Upon issue of a new technical card, the present one will no longer be valid.