Renove

Renoprimer Aqua

MULTIFUNCTIONAL PRIMER



PRODUCT INFORMATION PAGE

TECHNICAL DATA:

Nr. art. 0953

BASE:	synthetic dispersion
COLOUR:	white
DENSITY:	1,0 g/cm^3
WORKABILITY TEMPERATURE:	≥10°C
RECOMMENDED TOOLS:	brush or roller
COVERAGE:	about 75g/m^2 (at 1;1 ratio)
PACKAGING:	5kg, 10kg

- solvent free
- can be diluted with water
- upon modifications can feature as electric conductor

PROPERTIES AND APPLICATION:
Universal and multifunctional primer on the base of synthetic dispersion. Improves adhesion, closing pores on the porous and non-porous subfloors . Recommended on variety of subfloors as concrete, screeds, USB boards, ceramic boards, natural stone, synthetic stones. Can be used as an activator – adhesion agent for self-levelling and screed coating.

PRIMING:
The subfloor has to be solid, free from cracks, dry, and clean. The screed subfloor has to be polished and clean. The primer should be applied by the roller evenly. Avoid creating excess and paddles. Can be diluted with water in 1:1 ratio (In case of the very porous subfloors 1:3 ratio).

STORAGE:
Renoprimer Aqua must be cept in original packaging in cool and dry place. Keep away from frozen conditions. Follow the instructions given in this chart.

SHELVE LIFE:
6 months from the production date in original and closed package in temperature at 5°C to 25°C.

Accordingly to the current regulations, this product does not contain ingredients/components classified as harmful.

For difficult problem-solving questions, or products with special requirements, which are not covered by this technical card, we assure all our clients of our professional consulting services. Upon issue of a new technical card, the present one will no longer be valid.