Renove

Renoprimer PU-150

READY TO USE, FAST SETTING POLYURETHANE PRIMER



PRODUCT INFORMATION PAGE

TECHNICAL DATA:

Nr. art. 0947

BASE:	100 % Polyurethane
FORM:	liquid
COLOUR:	light brown
ODOUR:	specific
DENSITY:	1 g/cm^3
TEMPERATURE OF APPLICATION:	over 15°C
STEPPING ON ALLOWED:	after approx. 3 hours
SHELF LIFE:	24 months from the production date
PACKAGE SIZES:	5L

PROPERTIES:
Single-component polyurethane priming preparation containing a solvent, for use before adhesion of parquets with PU and MS glues. Strengthens cement and anhydrite ground layers. Seals the ground, concurrently protecting it against dusting. Improves glue adhesion to the ground. Deep penetrating.

APPLICATION:
For priming of dusty and absorbing cement and anhydrite grounds. Effective in surface strengthening, porosity reduction and adherence improvement. Suitable also for grounds with floor heating.

METHOD OF USE:
The ground and climatic conditions in the room must meet the guidelines of standard DIN 18356. Mix well by shaking prior to use. Do not dilute. Apply on dry and clean surfaces, free from oil, wax and other contamination. Apply evenly using a roller or brush - avoid creating puddles.

Glue application can be commenced after ca. 6 - 7 hours.

CONSUMPTION:
0.15 – 0.35 l/m^2 (for single priming)
0.25 – 0.60 l/m^2 (for double or triple priming).

STORAGE:
Store in originally sealed package, in a dry room, at the temperature at 5°C to 25°C. After long-term storage, mix the product before use.

For difficult problem-solving questions, or products with special requirements, which are not covered by this technical card, we assure all our clients of our professional consulting services. Upon issue of a new technical card, the present one will no longer be valid.