Renove

Renoprimer

PU-155 eco

ONE-COMPONENT, QUICK-DRYING POLYURETHANE PRIMER



PRODUCT INFORMATION PAGE

TECHNICAL DATA:

Nr. art. 0951

BASE:	100 % Polyurethane
FORM:	liquid
COLOUR:	light brown
ODOUR:	lightly scented
DENSITY:	0.98 g/cm^3
TEMPERATURE OF APPLICATION:	above 15°C
STEPPING ON ALLOWED:	after approx. 1 hours
SHELF LIFE:	12 months from the production date
PACKAGE SIZES:	5L

PROPERTIES:
Low-emission, lightly scented, one-component polyurethane primer for use before parquet bonding with PU and MS adhesives. It perfectly reinforces and deeply penetrates cement and anhydrite substrates. Seals, increasing the adhesion of the adhesive to the substrate.

INTENDED USE:
For priming dusty and absorbent cement and anhydrite substrates. Effectively strengthens the surface, reduces porosity and improves adhesion. It is also suitable for floors with underfloor heating.

METHOD OF USE:
The substrate and interior environment conditions must comply with DIN 18356. Mix well by shaking the container before use. Do not dilute. Apply to dry, clean surface, free of oil, wax and other dirt. Spread evenly with a roller or brush, avoid the formation of puddles.

Gluing can be started after approx. 1 hour.

CONSUMPTION:
0.15 – 0.35 l/m^2 (for single priming)
0.25 – 0.60 l/m^2 (for double or triple priming).

STORAGE:
Store in originally sealed package, in a dry room, at the temperature at 5°C to 25°C. After long-term storage, mix the product before use.

For difficult problem-solving questions, or products with special requirements, which are not covered by this technical card, we assure all our clients of our professional consulting services. Upon issue of a new technical card, the present one will no longer be valid.